

UL LISTED, LP-GAS 250 PSI, 400 PSI W.O.G.

### FISHER VALVES

- Ductile Iron Body
- TFE Chevron Packings
- Slip Joint Disc Seats
- Valve has 1/4" plugged opening  
(For relief valve, bleeder valve or gauge.)



N450 ANGLE VALVE



N301 GLOBE VALVE

RMI Part No.		FNPT Size
Globe Valve	Angle Valve	
N301-04	N401-04	1/2"
N301-06	N401-06	3/4"
N301-08	N401-08	1"
N310-10	N410-10	1 1/4"
N310-12	N410-12	1 1/2"
N310-16	N410-16	2"
N310-24	N410-24	3"
N310F-24	N410F-24	3" Flange
N350 & N450 ECONOMY SERIES		
N350-04	N450-04	1/2"
N350-06	N450-06	3/4"

### MARSHALL EXCELSIOR GLOBE AND ANGLE VALVE



ME815-6

- All stainless steel internal components
- Double stem seal design
- 1 1/4" and larger globe valves have 35° seat angle for maximum flow
- 1 1/4" and larger globe valves ergonomically designed

RMI Part No.		Size	Side Port	E-Z Turn Knob
GLOBE	ANGLE			
ME825-4	ME815-4	1/2"	1 x 1/4"	x
ME825-6	ME815-6	3/4"	1 x 1/4"	x
ME825-8	ME815-8	1"	1 x 1/4"	x
ME825-10	ME815-10	1 1/4"	2 x 1/4"	ME829
ME825-12	ME815-12	1 1/2"	2 x 1/4"	ME829
ME825-16	ME815-16	2"	2 x 1/4"	ME829
ME824-16		2"	2 x 1/2"	ME829
ME825-24	ME815-24	3"	2 x 1/4"	Included

### SQUIBB-TAYLOR FLANGED GLOBE AND ANGLE VALVES

- Spring loaded chevron packing
- 1/4" NPT plugged side port
- Self-aligning seat disc retainer



RMI Part No.		Size
GLOBE	ANGLE	
AL316FP	AL317FP	2"
AL320FP	AL321FP	3"

### APOLLO BALL VALVES



600 PSI WOG, 250 PSI LP Gas UL Listed economical valve for both liquid and vapor LP Gas service. Teflon packing and bearing, blow-out proof stem, chromium plated ball, cast bronze construction, large port opening.

RMI Part No.	Thread Size	Port Diameter	Valve Length
80-101	1/4"	3/8"	2 1/16"
80-102	3/8"	3/8"	2 1/16"
80-103	1/2"	1/2"	2 1/4"
80-104	3/4"	1 1/16"	3"
80-105	1"	7/8"	3 3/8"
80-106	1 1/4"	1"	4"
80-107	1 1/2"	1 1/4"	4 3/8"
80-108	2"	1 1/2"	4 11/16"
80-100	3"	2 1/2"	6 3/4"

### JOMAR FULL-PART BALL VALVES



Forged brass body with chrome plated ball. AGA & UL Listed. 500 PSI WOG 1" - 2 size 600 PSI WOG 1/4" - 3/4" size

RMI Part No.	Thread Size	Port Diameter	Valve Length
100-701	1/4"	3/8"	1 13/16"
100-702	3/8"	3/8"	1 7/8"
100-703	1/2"	1/2"	2 7/16"
100-704	3/4"	3/4"	2 11/16"
100-705	1"	1"	3 5/16"
100-706	1 1/4"	1 1/4"	3 13/16"
100-707	1 1/2"	1 1/2"	4 3/16"
100-708	2"	2"	5"
100-710	3"	3"	7.08"

### JOMAR UNION END BALL VALVES



Jomar valves feature full port flow, Teflon seats, Buna-N seals, and union ends for easy installation and low service and maintenance costs. Carbon steel body with forged carbon steel union ends. UL listed, LP-Gas 250 PSI, 400 PSI W.O.G.

RMI Part No.	Thread Size	Port	Length
100-991	1/4"	0.437	3.543
100-992	3/8"	0.437	3.543
100-993	1/2"	0.622	3.543
100-994	3/4"	0.807	3.701
100-995	1"	1.00	4.252
100-996	1 1/4"	1.25	4.567
100-997	1 1/2"	1.50	5.197
100-998	2"	1.969	5.669

### JOMAR 3-PIECE FULL PORT BALL VALVE



316 SS Body, ball and stem, pressure rated 1000 psig, UL listed for flammable liquids, propane, natural gas and anhydrous ammonia with locking handle.

RMI Part No.	Thread Size	Length
500-301	1/4"	2.36
500-302	3/8"	2.36
500-303	1/2"	2.76
500-304	3/4"	3.03
500-305	1	3.62
500-306	1 1/4"	4.13
500-307	1 1/2"	4.72
500-308	2	5.43
500-310	3	7.52
500-311	4	8.50

\* Carbon steel with threaded or socket weld ends are available ( 1/2" - 2").

### MARPAC UNION END BALL VALVES



CSE790TTU-1.5

Marpac valves feature full port flow, Teflon seats, Buna-N seals, and union ends for easy installation and low service and maintenance costs. Carbon steel body with forged carbon steel union ends.

RMI Part No.	Thread Size	Port Diameter	Valve Length
CSE790TTU-3/4	3/4"	13/16"	4 1/2"
CSE790TTU-1	1"	1"	5 15/16"
CSE790TTU-1.2	1 1/4"	1 1/4"	5 3/8"
CSE790TTU-1.5	1 1/2"	1 7/16"	5 7/8"
CSE790TTU-2	2"	1 3/4"	5 7/8"
DI-800-TT*	3"	2 5/8"	7 3/8"

\*Screwed ends - not union type.

### JOMAR STAINLESS STEEL VALVES

- Stainless Steel full port ball valve
- 316 SS ball and stem
- 1000psig pressure rating
- UL listed



RMI Part No.	Thread Size	Port Diameter	Valve Length
100-961	1/4"	0.43	2.21
100-962	3/8"	0.43	2.21
100-963	1/2"	0.56	2.60
100-964	3/4"	0.61	2.99
100-965	1"	1.00	3.54
100-966	1 1/4"	1.25	3.94
100-967	1 1/2"	1.50	4.41
100-968	2"	1.97	5.00

### JOMAR SINGLE UNION END VALVE

- Forged brass body
- 3/8" - 1" have 1/8" tap
- 1 1/4" - 2" have 1/4" tap
- FM and CSA approved



RMI Part No.	Thread Size	Port Diameter	Valve Length
160-102	3/8"	0.39	2.93
160-103	1/2"	0.59	3.17
160-104	3/4"	0.79	3.52
160-105	1"	1.00	4.19
160-106	1 1/4"	1.26	5.01
160-107	1 1/2"	1.57	5.57
160-108	2"	2.00	6.31

### APOLLO BALL VALVE WITH SPRING RETURN HANDLE

- Excellent for bleed lines and blow offs
- All components of lever are stainless steel
- Brass valves are rated for 600psig
- Stainless valves are rated for 200psig up to 1" and 1500psig 1 1/4" - 2"



RMI Part No.		Size
Brass	Stainless	
71-501-01	76-501-01	1/4"
71-502-01	76-502-01	3/8"
71-503-01	76-503-01	1/2"
71-504-01	76-504-01	3/4"
71-505-01	76-505-01	1"
71-506-01	76-506-01	1 1/4"
71-507-01	76-507-01	1 1/2"
71-508-01	76-508-01	2"

## JOMAR CARBON STEEL FLANGED BALL VALVE

1/4 turn, WCB Carbon Steel body, 316 Stainless Steel ball and stem, 100% full port, blowout proof stem, 2-piece body design.

### Features:

- Full Port
- PTFE Seats
- API 607 (fire tite)
- 316 Stainless Ball and Stem
- 150# Flanged Valves are available
- Available up to 8"
- Stainless Steel Valves are Available



### WARNING:

Do not lock valve handle in **OPEN** position on natural gas hazardous service.

RMI Part No.	Description
600-228	2" Full Port 300# Ball Valve
600-230	3" Full Port 300# Ball Valve
600-231	4" Full Port 300# Ball Valve

## APOLLO 300 LB. FLANGED FULL-PORT BALL VALVES



- Full-port body
- Antistatic grounded stem
- Cast bosses for bleed/drain ports
- Slot vent for thermal expansion
- Two-position locking device

### Also available:

- Other sizes
- 150 lb flanges
- Standard port valves
- 316SS ball and stem
- Fire Safe (graphite packing and seal)

RMI Part No.	Flange Size	Port Diameter	Length
88A-908-01	2"	2.00	8.50
88A-900-01	3"	3.00	11.12
88A-90A-01	4"	4.00	12.00

## SOLENOID VALVES

Magnetrol solenoid valves are available as a special order. These heavy-duty valves are available in sizes from 1/2" - 3", are explosion proof and have operating pressures to 500PSIG.

**When requesting a quote for the valves, please specify the following five variables:**

- Line size
- Voltage
- Normally open or closed
- Service
- Operating Pressure



## 3-WAY VALVE



- Stainless Steel Construction
- L-Port Design
- 800 PSI WOG
- Positive position location @ 90° increments
- Domestic Manufacturer
- Ideal for 2 Hose Fill Stations
- Other sizes available as a special order

RMI Part No.	Description
MPT-365-1/2*	1/2" 3-Way Ball Valve
MPT-1/075	3/4" 3-Way Ball Valve
3L380000RTTS100	1" 3-Way Ball Valve
MPT-1/125	1 1/4" 3-Way Ball Valve
MPT-1/150	1 1/2" 3-Way Ball Valve
MPT100-L	2" 3-Way Ball Valve

\*Brass Construction