



MEC Gas Box (High Pressure)

APPLICATION

Utilizes standard LP Gas outdoor appliance regulator and connector. Both models provide full capacity operation at 10 PSI or higher inlet pressure for all outdoor appliances without modification or the hassles of a 20 lb. cylinder. Simply thread the Type 1 QCC or POL connector onto the MEC Gas Box, turn on the shutoff valve, wait approximately 60 seconds and enjoy continuous LP Gas flow.

FEATURES

- Universal 1 5/16" M. ACME/F. POL Outlet
- Primary Shutoff Valve for each Outlet Connection
- For use with 10-250 PSI Inlet Pressure
- Universal Mounting Hardware
- Weather Resistant Nylon Case
- Universal 1/2" FNPT Inlet Connection
- Secondary Safety shutoff Poppet at each Outlet for Zero Discharge at Disconnect
- Hinged Cover with Latching Mechanism



ME951BLK

Model No.	Description	Color
ME951BLK	Single 1 5/16" M. ACME/F. POL w/1/2" FNPT Inlet	Black
ME951GRY	Single 1 5/16" M. ACME/F. POL w/1/2" FNPT Inlet	Grey
ME951IVY	Single 1 5/16" M. ACME/F. POL w/1/2" FNPT Inlet	Ivory
ME952BLK	Dual 1 5/16" M. ACME/F. POL w/1/2" FNPT Inlet	Black
ME952GRY	Dual 1 5/16" M. ACME/F. POL w/1/2" FNPT Inlet	Grey
ME952IVY	Dual 1 5/16" M. ACME/F. POL w/1/2" FNPT Inlet	Ivory



ME952GRY Installed

Model No.	Description	Length
MER428-60	Extension hose assembly (M. QCC/F. POL x F. QCC)	60"
MER428-120	Extension hose assembly (M. QCC/F. POL x F. QCC)	120"



PROPANE CYLINDERS

Model No.	Description
11-TYPE1-OPD	11# Light Compact Cylinder
20-TYPE1-OPD	20# Steel Cylinder
30-TYPE1-OPD	30# Steel Cylinder
40-TYPE1-OPD	40# Steel Cylinder
50HC-10	50# Cylinder w/POL Valve
100HC-M	100# Cylinder w/Multi Valve

Note: Other container sizes available



Call for cylinder information and pricing.

SOME BRANDS ARE ONLY AVAILABLE IN SELECTED AREAS, SEE PAGE 6 OR CONTACT YOUR REGIONAL SALES MANAGER FOR MORE INFO.
Pricing, model numbers and availability are subject to change without notice.