



GASKIT - REG

LEAK DETECTOR

Lab proven "stainless-friendly" leak detector. Stainless-friendly (chloride and fluoride free). All leak detectors are not the same - GasKit formula was developed to NOT corrode and cause pin holes especially in flexible CSST also others may have. RMI exclusive.

Also available in 55 gallon drums - drop shipped from factory.



GAS KIT LEAK DETECTOR

RMI Part No.	Description	Color
GASKIT-REG	Regular (27°)-1 Gallon	Green
GASKIT-LT	LoTemp (10°)-1 Gallon	Pink
GASKIT-XL	Extra Lo Temp (-50°)-1 Gallon	Red
GASKIT-CG	Green for O ₂ (27°)-1 Gallon	Blue
GASKIT-TYPE II	Lo Temp Oxy (-65°)-1 Gallon	Lt. Blue

CYLINDER ACCESSORIES

BRUSH, SQUEEZE & SPRAY BOTTLES



LD-SPRAY



WP110, 120



LD-BOTTLE

- Wide neck bottle and brush for easy application.
- Pint bottle with spray nozzle.
- Handy squeeze bottles.

RMI Part No.	Description
LD-BOTTLE	Empty Pint Bottle & Brush
LD-SPRAY	Empty Pint Bottle w/ Sprayer
LD-DAUBER	8 oz. Bottle and Dauber
WP110	4 oz. Empty Squeeze Bottle
WP120	8 oz. Empty Squeeze Bottle

THREAD SEALANTS

OC-3

Use Oxygen compatible OC Three to seal threaded connections on cylinder valves more effectively and safely than Teflon tape.

OC-5

Use Oxygen compatible OC Five to seal threaded connections on high pressure cylinder valves or cryogenic applications. OC Five will also seal threaded connections on large diameter pipes or more course threads.

OC-7

Use Oxygen compatible OC Seven to lubricate O-rings, gaskets, bearings, stop cocks and more. OC Seven can be used as a high vacuum grease.

All OC products are approved by the major industrial gas providers.



O2TT-1/2

RMI PART NO.	DESCRIPTION
OC-3	PTFE Paste 4 oz. Tube
OC-5	PTFE Paste 2 oz. Jar
OC-5-16	PTFE Paste 16 oz. Jar
OC-7	PTFE Grease 2 oz. Jar
OC-7-16	PTFE Grease 16 oz. Jar
O2TT-1/2	Green oxygen Teflon thread seal tape 1/2" x 520
O2TT-3/4	Green oxygen Teflon thread seal tape 3/4" x 520



OC-3



OC-5



OC-7

© Ray Murray Inc. Edition 11