



BOBTAIL DELIVERY HOSE WITH FACTORY CRIMPED PRO-SUR BRASS ENDS

RMI Part No.	I.D.	O.D.	Length	Shipping Weight (Lbs.) per Length
TLPGH-1-100CT*	1"	1 1/2"	100'	63
TLPGH-1-125CT	1"	1 1/2"	125'	77
TLPGH-1-150CT	1"	1 1/2"	150'	92
TLPGH-1-175CT	1"	1 1/2"	175'	102
TLPGH-3/4-125CT	3/4"	1 1/4"	125'	59
TLPGH-3/4-150CT	3/4"	1 1/4"	150'	70
TLPGH-3/4-175CT*	3/4"	1 1/4"	175'	80

* Available as Special Order.

POLAR FLEX LOW-TEMP (-50°F) DELIVERY HOSE WITH FACTORY PRESSURE TESTED CRIMPED BRASS ENDS

RMI Part No.	I.D.	O.D.	Length	Shipping Weight (Lbs.) per Length
TLPGH-1-125CTPF	1"	1 1/2"	125'	77
TLPGH-1-150CTPF	1"	1 1/2"	150'	92

- UL-21 approved
- 350 max. WP 1750 min. burst
- Smooth cover, Thermalon
- Oil resistant and flame retardant
- -40° to 180° F
- Four-spiral reinforcement
- Tested to DOT requirements



PARKER BOBTAIL HOSE

- UL-21 approved
- 350 max. WP 1750 min. burst
- Smooth cover, Thermalon
- Oil resistant and flame retardant
- -40° to 180° F
- Four-spiral reinforced
- Tested to DOT requirements

BOBTAIL DELIVERY HOSE WITH FACTORY PRESSURE TESTED CRIMPED ENDS


RMI Part No.	I.D.	O.D.	Length	Shipping Weight (Lbs.) per Length
LPGH-1-125CT	1"	1 1/2"	125'	80
LPGH-1-150CT	1"	1 1/2"	150'	95
LPGH-3/4-125CT	3/4"	1 1/4"	125'	70
LPGH-3/4-150CT	3/4"	1 1/4"	150'	83

PARKER EXTREME BOBTAIL HOSE

- -65° to 180° F
- Neoprene cover

PARKER EXTREME LOW TEMPERATURE HOSE

RMI Part No.	I.D.	O.D.	Length	Shipping Weight (Lbs.) per Length
EXLPGH-1-125CT	1"		125'	80
EXLPGH-1-150CT	1"		150'	95



Smart-Hose shown during normal delivery operation

Hose break

De-coupling

Smart-Hose shown in failure situations, instantly shutting down the flow

SMART-HOSE PASSIVE SHUTDOWN SYSTEM - DOT & FACILITY HOSE

The Smart-Hose meets the requirements of the DOT standards and additions to NFPA for a passive shut-down system. The patented system features an internal cable connected to normally unseated "valve plungers or wedges" located on each end of the cable. In the event of coupling-to-hose separation, stretching to the point of an unsafe condition or hose severance, the valve "wedges" are released and instantly seat, stopping the flow in both directions.

- Complies with HM-225
- Provides advanced safety
- Prevents loss of product
- Prevents property damage
- No added field maintenance beyond normal hose inspection
- Factory recoupling program available

LIFELINE BREAK-AWAY FEATURE

- Available for 2" dot or facility hose
- Engineered break-away point
- Factory rebuildable

1" SMART-HOSE ASSEMBLIES

RMI Part No.	Description
CG-LPG-16-R10	1" x 10' Smart-Hose
CG-LPG-16-R15	1" x 15' Smart-Hose
CG-LPG-16-R20	1" x 20' Smart-Hose
CG-LPG-16-R25	1" x 25' Smart-Hose
CG-LPG-16-R30	1" x 30' Smart-Hose

1 1/4" SMART-HOSE ASSEMBLIES

RMI Part No.	Description
CG-LPG-20-R10	1 1/4" x 10' Smart-Hose
CG-LPG-20-R15	1 1/4" x 15' Smart-Hose
CG-LPG-20-R20	1 1/4" x 20' Smart-Hose
CG-LPG-20-R25	1 1/4" x 25' Smart-Hose
CG-LPG-20-R30	1 1/4" x 30' Smart-Hose

2" SMART-HOSE ASSEMBLIES WITH BREAK AWAY

RMI Part No.	Description
CG-LPG-32-BR15-3	1" x 10' Smart-Hose
CG-LPG-32-BR20-3	1" x 15' Smart-Hose

FACILITY HOSE

RMI Part No.	Description
CG-LPG-32-R10-3F	2" x 10' Facility-Hose*
CG-LPG-32-R15-3F	2" x 15' Facility-Hose*

*Not for DOT applications.

2" SMART-HOSE ASSEMBLIES


RMI Part No.	Description
CG-LPG-32-R10-3	2" x 10' Lifeline 3
CG-LPG-32-R15-3	2" x 15' Lifeline 3
CG-LPG-32-R20-3	2" x 18.5' Lifeline 3
CG-LPG-32-R25-3	2" x 25' Lifeline 3
CG-LPG-32-R30-3	2" x 30' Lifeline 3

FACILITY HOSE WITH BREAK AWAY

RMI Part No.	Description
CG-LPG-32-BR12-3F	2" x 12' Facility Hose
CG-LPG-32-BR15-3F	2" x 15' Facility Hose

2" SMART-HOSE ASSEMBLIES FOR NH3

RMI Part No.	Description
CG-NH3-32-R20-3	2" X 18.5 Smart-Hose for NH3
CG-NH3-SS-32-R18.5-3	2" X 18.5' Smart-Hose S/S Braid for NH3



HOSE INFORMATION

- Hose manufacturers do not recommend the use of screw-in type reusable couplings.
- The cover of all LP-gas hose must be perforated to prevent gas build-up among the various layers of the hose.
- LP-gas hose can be used for natural gas service in outdoor applications only, and at a maximum pressure of 50 PSI.

DAYCO

DAYCO/PARKER BRAND HOSE

- UL-21 approved
- 350 max. WP 1750 min. burst
- Smooth cover, Thermalon
- Abrasive resistant
- -40° to 180° F

RMI Part No.	I.D.	O.D.	Weight (Lbs.) per 100 Foot
LPGH-1/4	1/4"	.610"	14
LPGH-3/8	3/8"	.750"	22
LPGH-1/2	1/2"	.937"	30
LPGH-3/4	3/4"	1 1/4"	53
LPGH-1	1"	1 1/2"	66

NOTE: Bulk hose reel lengths can be up to 3 random lengths totaling approximately 500-700 feet.

ACCUFLEX THERMOPLASTIC HOSE


RMI Part No.	I.D.	O.D.	Weight (Lbs.) per 100 Foot
LPGH-5/16	5/16"	.580"	16

RMI CRIMPED HOSE ASSEMBLIES

RMI factory trained personnel will make crimped hose assemblies to your requirements.

RMI Part No.	Hose I.D.	Thread Size	Min. Length
1/4 Hosekit	1/4"	1/4"	6"
3/8 Hosekit	3/8"	3/8"	6"
1/2 Hosekit	1/2"	1/2"	6 3/4"
3/4 Hosekit	3/4"	3/4"	6 3/4"
1 Hosekit	1"	1"	7"
1 1/4 Hosekit	1 1/4"	1 1/4"	9"
1 1/2 Hosekit	1 1/2"	1 1/2"	9 1/2"
2 Hosekit	2"	2"	11 1/4"

DAYCO BULK TRANSFER HOSE



- UL 21 Approved
- 350 maximum working pressure
- 1750 min. burst
- Wrapped impression neoprene cover
- 3-braid reinforcement

RMI Part No.	I.D.	O.D.	Weight (Lbs.) per 100 Foot
LPGH-1 1/4	1 1/4"	1 7/8"	95
LPGH-1 1/2	1 1/2"	1 25/32"	125
LPGH-2	2"	2 3/4"	170

PROWRAP HOSE PROTECTION

- Easy to install
- Tight grip prevents sliding
- -70° F - 180° F
- UV resistant



RMI Part No.	Description
PWLD-16	66 ft. length 1/4" - 3/4" Hose
PWLD-20	12.5 ft. length 1" - 1 1/4" Hose
PWLD-32	12.5 ft. length 1 1/2" x 2" Hose



If you require a hose assembly to be tested to DOT requirements, they can be made up to the sizes listed below.

RMI Part No.	Hose I.D.	Thread Size	Min. Length	Max. Length
3/4 Hosekit-Tested	3/4"	3/4"	6 3/4"	50 ft.
1 Hosekit-Tested	1"	1"	7"	50 ft.
1 1/4 Hosekit-Tested	1 1/4"	1 1/4"	9"	40 ft.
1 1/2 Hosekit-Tested	1 1/2"	1 1/2"	9 1/2"	30 ft.
2 Hosekit-Tested	2"	2"	11 1/4"	30 ft.

(note: custom wire braid flex connectors can be made)



SWIVEL ACME HOSE COUPLING

ME3162 SERIES

RMI Part No.		Material	Hose I.D.	F. ACME Size
Marshall Excelsior	Fisher			
ME3162-32S	M3162-32S	Steel	2"	3 1/4"
ME3162-32B	M3162-32B	Brass	2"	3 1/4"

RMI offers Fisher parts and, in some cases, Marshall Excelsior as a competitively priced alternative.

PIPE TO HOSE SWIVEL ADAPTORS



107 MALE ADAPTOR



207 FEMALE ADAPTOR

RMI Part No.		NPT Pipe x NPS Swivel
Male Adaptor	Female Adaptor	
107-8-8	207-8-8	1/2"
107-12-12	207-12-12	3/4"
107-16-16	207-16-16	1"
107-20-20	207-20-20	1 1/4"
107-24-24	207-24-24	1 1/2"
107-32-32	207-32-32	2"

LPG STAINLESS STEEL BRAID HOSE WITH CLOTH

Seamless oil resistant synthetic rubber high temperature tube. One stainless steel wire braid and two polyester braids. The cloth cover is impregnated with fire- and mildew-resistant compounds



RMI Part No.	I.D.	O.D.	Working Pressure	Burst Pressure
SS25UL-4	3/16"	.52	350	1750
SS25UL-5	1/4"	.58	350	1750
SS25UL-6	5/16"	.67	350	1750
SS25UL-8	13/32"	.77	350	1750
SS25UL-10	1/2"	.92	350	1750
SS25UL-12	5/8"	1.08	350	1750



BH-38



BHT-38



BHT-14

BRASS BULKHEAD FITTINGS

RMI Part No.	Description
BH-38	3/8" Flair Straight Through
BHT-38	3/8" Flare x (2) 1/4" NPT Tee
BHT-14	1/4" Flare x (2) 1/4" NPT Tee

TWO-BOLT CLAMP TYPE HOSE COUPLING




ME3162 Series

RMI Part No.		Hose I.D.	Thread Size
Marshall Excelsior	Fisher		
ME3162-08	M3162-08	1/2"	1/2"
ME3162-12	M3162-12	3/4"	3/4"
ME3162-16	M3162-16	1"	1"
ME3162-20	M3162-20	1 1/4"	1 1/4"
ME3162-24	M3162-24	1 1/2"	1 1/2"
ME3162-32	M3162-32	2"	2"
	M3162-48	3"	3"

FEMALE ANGLE FLARE FITTING FOR STAINLESS BRAID MOTOR HOSE



27720-6



27920-6

RMI Part No.	Hose I.D.	Female Flare Size	Angle
27720-6	5/16"	3/8"	45°
27920-6	5/16"	3/8"	90°

HOSE ENDS FOR STAINLESS BRAID FOR MOTOR FUEL HOSE



20820



20120

RMI Part No.	Hose I.D.	Female 45° Flare
20820-4	3/16"	1/4"
20820-5	1/4"	1/4"
20820-6	5/16"	1/4"
20820-8	13/32"	1/2"
20820-8-10	1/2"	1/2"
20820-10	1/2"	5/8"
20820-12-12	5/8"	3/4"

RMI Part No.	Hose I.D.	Male NPT
20120-4-4	3/16"	1/4"
20120-4-5	1/4"	1/4"
20120-4-6	5/16"	1/4"
20120-8-8	13/32"	1/2"
20120-8-10	1/2"	1/2"
20120-12-10	1/2"	3/4"
20120-12-12	5/8"	3/4"